CBS8000-64-96KWH

64 / 80 / 96 KWH

Smart battery cabinet



We've GOT YOU COVERED with CGL insurance.

Simplicity

- Pre-installed in factory for easy installation on site
- Effortless operation, cloud control

Safety

- IP55 protect rating and C4 corrosion resistance
- Double fire suppression system design

Flexibility

- Single cabinet capacity of 64/80/96kWh
- Up to 4 cabinet in parallel (Max. 384kWh)

Robustness

- Max. 46.08kW charging/discharging power
- Active balancing for each battery module

www.sofarsolar.com

© As of May 2026, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

Model	CBS8000-64KWH	CBS8000-80KWH	CBS8000-96KWH
Battery			
Battery Type[1]		$LiFePO_4$	
Rated Capacity		314Ah	
Max. Charging Current		150A	
Max. Discharging Current		200A	
Pack Configuration		1P16S	
Nominal Voltage		600Vd.c	
Pack Quantity	4 Pack/Cluster	5 Pack/Cluster	6 Pack/Cluster
Battery Total Energy[2]	64.31kWh	80.38kWh	96.46kWh
Rated Power	30.72kW	38.40kW	46.08kW
System			
Protective Class		Class I	
IP Rating		IP55	
Anti-Corrosion Grade		C4	
Operating Temperature Range[3]		-20˚C ~ +50˚C (Derating above +45˚C)	
Relative Humidity Range		5%-95%	
Max. Operating Altitude[4]		3000m	
Installation		Floor Mounted	
Communication		CAN	
Cooling Mode		Intelligent Airflow	
Air Conditioner Power		1.5kW (Cooling), 1kW (Heating)	
Noise		65dB (Typical)	
Fire Protection		Aerogel (Optional Perfluorohexanone)	
Dimensions (W×H×D)		750×2100×1150mm (±20mm)	
Weight	870kg	980kg	1090kg

[1] Rechargeable Li-ion Battery system.
[2] Test conditions: 0.2C charging/discharging at 25˚C, 100%DOD.
[3] Refer to the temperature derating curve and the battery needs to enable heating function if it needs to be charge when temperature is blow 0˚C.
[4] If the altitude is >2000m, derating operation is required, refer to the derating curve.

*All specifications are subject to change without notice.